

# CHARGING POLE eMC2 44 kW

With its attractive, extremely weatherproof and powder coated metal housing, the eMC2 charging pole is the ideal solution for semi-public installations. The eMC2 has two Type 2 charging sockets with a charging capacity of up to 22 kW per charging point. Charging access is controlled via RFID.

Of course, the eMC2 comes with our DC fault current detection installed as standard. With a choice of separately available charging cables (Type 2 to Type 2, Type 2 to Type 1), the system offers flexible charging of various types of electric vehicles.

The optional prefabricated foundation minimizes onsite technical requirements and installation time.



## General information

Model	eMC2
Part number	2P4403
Item number (EAN)	-
Commodity code	85371091
Packaging unit (PU)	1 unit
Includes	EMC2 charging pole, instruction manual

## Input/Supply

Power supply	for supply cable sizes up to 5 x 70 mm <sup>2</sup>
Rated voltage	230 / 400 V
Rated current	63 A
Rated frequency	50 Hz
Back-up fuse	63 A
Terminal block	up to 70 mm <sup>2</sup>

## Output/vehicle connection

Connection system	Lockable Type 2 charging socket, 32 A, in acc. with IEC62196-2; 2 pcs.
Output voltage	230 / 400 V
Max. charging current	32 A
Maximum output	22 kW
Shut down (Standby)	all poles
Load management	-
Unlocking module	automatically unlocks the charging socket in case of a power failure

## Protection/integrated components

MCB	32 A, 3-pole, C characteristic, 2 pcs.
RCCB	FI-RCCB, Type A, 30 mA, 2 pcs.
DC fault current detection	electronic, $I_{\Delta n \text{ d.c.}} \geq 6 \text{ mA}$
Energy meter	-
Installation contactor	4-pole

## Charge control/status indicators

Charge controller	EVCC, 2 pcs.
Communication	in acc. with IEC 61851-1, Mode 3
Status display	LED (available or in use)
Operating status indicator	LED (stand-by, EV detected, charging)
Firmware indicator	LED (flashes on startup)
Fault indicator	LED (various flash patterns)
Interface	RS485
RFID card reader	integrated, communication via Mifare Ultralight and Mifare Desfire
Communication	-

## Standards/Directives

IEC 61851-1 Ed 2.0:2010

## Operating conditions

Storage temperature	-30°C to 85°C
Operating temperature	-30°C to 50°C
Relative humidity	5 to 95%, no condensation
Class of protection	I
Overvoltage category	III
Pollution degree	3
Degree of protection (housing)	IP44
Power dissipation	n/a

## Housing

Type	Mounting pole
Fixing type	Screw fixings to pre-fabricated foundation (foundation not included)
Material (housing)	Steel
Housing color	Powder coated DB703
Material (cover)	Steel
Cover color	Powder coated DB701
Locking mechanism	Grip handle, prepared for the installation of a profile cylinder lock
Pole dimensions (HxWxD)	1,460 x 440 x 200 mm
Weight	ca. 44 kg

## Accessories

Type 2 charging cable	LAK32A3
Adapter cable	LAKK2K1
Prefabricated foundation	EMC9999
Pedestal, long	EMC9998
Pedestal, short	EMC9997
Lightning protection module	optional

## Dimensioned drawing

